



NOTES

1, WALL THICKNESS 0.76/1.02 UNLESS OTHERWISE STATED

1, MATERIAL & FINISH

18304/A ALUMINIUM LM31 PER BS EN 1559-1, 1559-4, 1676, 1706  
BLAST - STEEL SHOT

18304/B BRASS MB1 PER ASTM B 584  
BLAST - 60/40 ALUMINA GRIT

3, ELECTRICAL SPEC:

FREQUENCY: 12.4 - 18.0 GHz  
VSWR: 1.10 : 1 MAX

USED ON	TITLE	MATERIAL	FINISH	TOLERANCES	ORIGINAL SCALE	APP'D E	N/A				
PART No. 18304	WG18 60° E BEND REDUCED WALL (SKT TO SUIT A WG WALL OF .020")	SEE NOTE	SEE NOTE	Gen tol ±0.15	2 : 1	APP'D M	N/A	2	24-6-14	ADD ELEC SPEC, ECR5042, BY N.K, 24-6-14	
DRG No. CS17223						CHECKED	N/A	1	6-1-11		
SHT 1 OF 1	DRG SIZE A3			UNLESS OTHERWISE STATED, DIM'S ARE IN MILLIMETERS		DO NOT SCALE THIS PRINT					
						DRAWN	STR	6-1-11	ISS	DATE	DESC'N OF CHANGE or DCR No.

THIS DRAWING IS THE PROPERTY OF SYLATECH AND MUST NOT BE REPRODUCED WITHOUT PRIOR WRITTEN APPROVAL