



NOTES.

1, ELECTRICAL SPEC:  
 FREQUENCY: 15.0 - 22.0GHz  
 VSWR: 1.10 : 1 MAX

2, GEN WALL THICKNESS 1.02mm U.D.S.

THIS DRAWING IS THE PROPERTY OF SYLATECH AND MUST NOT BE REPRODUCED WITHOUT PRIOR WRITTEN APPROVAL

SYLATECH PART No.	MATERIAL	FINISH
19001/A	ALUMINIUM LM31 AS PER BS EN 1559-1, 1559-4, 1676, 1706.	STEEL SHOT BLAST
19001/B	BRASS MB1 AS PER ASTM B 584	60/40 ALUMINIA GRIT BLAST
19001/R	ALUMINIUM 3003	STEEL SHOT BLAST

APP'D E			3	24-6-14	ADD ELEC SPEC AND WALL THICKNESS NOTE. ECR5042, BY N.K., 24-6-14
APP'D M			2	22-6-11	REDRAW ON CADKEY AND ADD MATL/FINISH TABLE, ADD NOTE ABOUT SKT DETAIL BY NK ON 21-6-11 SEE DCR 4688
CHECKED			1	19-3-81	
DRAWN	NIC	19-3-81	ISS	DATE	DESCRIPTION OF CHANGE or DCR No.

USED ON	TITLE
PART No. 19001	WG19 'H' BEND OUTLINE DRG
DRG No. CS1453	
SHT 1 OF 1 DRG SIZE A4	

MATERIAL	FINISH	TOLERANCES	ORIGINAL SCALE
SEE TABLE	SEE TABLE	GEN ± 0.25 ANG ± 0.5°	3 : 1
DO NOT SCALE THIS PRINT UNLESS OTHERWISE STATED, DIM'NS ARE IN MILLIMETERS			